

WaveMon RF-60



Personal RF Monitor 100 kHz – 60 GHz



OCCUPATIONAL & PUBLIC RF SAFETY STANDARDS
ICNIRP, FCC, Directive 2013/35/EU, SC6, NATO



OVEREXPOSURE WARNING
From instant and average values



ELECTRIC AND MAGNETIC FIELD
Isotropic, RMS, shaped response



DATALOGGER
Including GPS and altimeter data



Compliance
with ITU-T K.145



Ready for 5G
measurements



Data
geolocation



Harness, Belt, or Arm Holder

RF Absorber Integrated in Holder

Datalogger for exposure studies
Instant and average values

Rechargeable and Replaceable
Batteries for 200 h Autonomy

GPS and Altimeter
(Optional)

E & H-Field Isotropic Sensors
with RMS Response

Exposure % of the Standard

ON/OFF Status Button

High Intensity Audible
and Vibratory Warnings

USB and Tripod Connectors



Worker's safety



Telecommunications



Railway



Medical



Labs



Aeronautical



Industry



Defense



Optional accredited calibration

Technical Specifications

Sensor type	Isotropic, RMS diode technology
Frequency	E-Field: 100 kHz – 60 GHz (see version selection table in next page) H-Field: 3 MHz – 1 GHz (see version selection table in next page)
Response	Shaped to specific standards (see version selection table in next page)
Isotropic deviation	E-Field: ± 1 dB (<4 GHz) H-Field: ± 1 dB
Dynamic Range	Up to 1000% (see version selection table in next page)
Linearity	E-Field: 0.5 dB (2% – 200%) H-Field: 0.5 dB (5% – 200%)
Interface	1 button ON/OFF, status and low battery LED
Indicators	6 LEDs + Audio + Vibration
Alarm threshold	2 alarm thresholds adjustable by user
Connectivity	Waterproof USB (for downloading data and recharging)
Falling detection	Yes
Autonomy	>1 month (at 8 h/day, 5 days/week)
Data logger	>1 000 000 events
Positioning	GPS and Altimeter (Optional)
Logging Interval	1 second to 60 minutes (adjustable by user)
Averaging Interval	1 second to 60 minutes (adjustable by user)
Battery Type	2 x AA NiMH battery rechargeable by USB
Protection	IP 54
LF immunity (50 / 60 Hz)	> 30 kV/m
Temperature range	-20 / +50 °C (-4 / +122 °F) – Charging: 0 / +40 °C (+32 / +104 °F)
Humidity	5% to 95%, non-condensing
Size	174 x 42.5 x 33 mm (6.8 x 1.7 x 1.3 ")
Weight	190 g (6.7 oz.)

Product specifications and descriptions in this document subject to change without notice.

WaveMon RF-60

WaveMon Version Selection Table

Versions	Response shaped to	E Field		H Field	
		Frequency response	Dynamic range	Frequency response	Dynamic range
RF-60 ICN	ICNIRP 1998/2020 * Occupational	±3.5 dB (100 kHz – 10 GHz) ±4 dB (10 GHz – 35 GHz) +10 / -6 dB (35 GHz – 60 GHz)	0.5 – 1000%	±3 dB (25 MHz – 1 GHz)	1 – 1000%
	ICNIRP 1998/2020 * General public	±3.5 dB (5 MHz – 10 GHz) ±4 dB (10 GHz – 35 GHz) +10 / -6 dB (35 GHz – 60 GHz)	0.5 – 1000%	±3 dB (25 MHz – 1 GHz)	3 – 1000%
RF-60 FCC	FCC 96-326 Occupational	±3.5 dB (100 kHz – 10 GHz) ±4 dB (10 GHz – 35 GHz) +10 / -6 dB (35 GHz – 60 GHz)	0.5 – 1000%	±2 dB (3 MHz – 1 GHz)	1 – 1000%
	FCC 96-326 General public	±5 dB (100 kHz – 2 MHz) ±3.5 dB (2 MHz – 10 GHz) ±4 dB (10 GHz – 35 GHz) +10 / -6 dB (35 GHz – 60 GHz)	0.5 – 1000%	±2 dB (3 MHz – 1 GHz)	3 – 1000%
RF-60 EUD	EU Directive 2013/35	±3.5 dB (100 kHz – 10 GHz) ±4 dB (10 GHz – 35 GHz) +10 / -6 dB (35 GHz – 60 GHz)	0.5 – 1000%	±3 dB (25 MHz – 1 GHz)	1 – 1000%
	Recommendation 1999/519/EC	±3.5 dB (5 MHz – 10 GHz) ±4 dB (10 GHz – 35 GHz) +10 / -6 dB (35 GHz – 60 GHz)	0.5 – 1000%	±3 dB (25 MHz – 1 GHz)	3 – 1000%
RF-60 SC6	Safety Code 6 Controlled	±3.5 dB (5 MHz – 10 GHz) ±4 dB (10 GHz – 35 GHz) +11 / -6 dB (35 GHz – 60 GHz)	0.5 – 1000%	±2 dB (25 MHz – 1 GHz)	1 – 1000%
	Safety Code 6 Uncontrolled	±3.5 dB (5 MHz – 10 GHz) ±4 dB (10 GHz – 35 GHz) +11 / -6 dB (35 GHz – 60 GHz)	0.5 – 1000%	±2 dB (25 MHz – 1 GHz)	3 – 1000%
RF-60 NATO	NATO standards Zone 1	±3.5 dB (100 kHz – 10 GHz) ±5 dB (10 GHz – 35 GHz) +12 / -6 dB (35 GHz – 60 GHz)	0.5 – 1000%	±2 dB (100 MHz – 1 GHz)	1 – 1000%

* compliant with ICNIRP 2020 from 27 MHz

WaveMon accessories



GPS
Part # W-WAVEMON-GPS

WaveMon Internal GPS



WaveStick
Part # WWMA0002

Adjustable extension stick (73 cm / 28,74 ")



Safety cable
Part # WWMA0001

WaveMon safety attachment cable

WaveMon_RF-60_EN_2103_v2.1